


























How to order Codifica

SPM	B	KC	4	J	TE	N	N
Series <i>Serie</i>	Size <i>Taglia</i>	Power <i>Potenza</i>	Poles <i>Poli</i>	Mounting <i>Montaggio</i>	Tension <i>Tensione</i>	Cooling <i>Raffreddamento</i>	Coating <i>Rivestimento</i>
SPM	B → 63	KC → 0.12	2 4 6	B14	Three-phase <i>Trifase</i>	N TENV (Non ventilato) 	N Without coating Senza rivestimento
	C → 71	KD → 0.18			TE 230/400V 50 Hz		
	D → 80	KE → 0.25		J → IMB14	TU 230/460V 60 Hz		
	E → 90	KF → 0.37		K → IMV18	On request <i>A richiesta</i>		
	F → 100	KG → 0.55		L → IMV19	TC 332/575V 60 Hz		
		KH → 0.75		B5	TD 220/380V 60 Hz		
		KI → 1.1			See our website for technical data <i>Vedere il nostro sito web per la documentazione tecnica</i>		
		KK → 1.5		G → IMB5			
		KL → 2.2		H → IMV1			
		KM → 3.0		I → IMV3			
		B3 With feet					
							
		P → IMB34					
		Q → IMV15					
		R → IMV36					
		For more info on mounting position, see page 9-6 <i>Per maggiori informazioni sulla posizione di montaggio, vedere pagina 9-6</i>					
			V TEFC (ventilato) 				

4	K	S	A	1	-N	-	--
Efficiency <i>Efficienza</i>	Protection <i>Protezione</i>	Terminal box <i>Morsettiera</i>	Cable gland position <i>Posizione pressacavo</i>	Cable gland type <i>Tipo di pressacavo</i>	Cable <i>cavo</i>	Thermal protection <i>Protezione termica termica</i>	Humid rooms options <i>Opzioni ambienti umidi</i>
4 IE4 efficiency <i>(Premium)</i>	K IP69k	S Terminal blocks 4+3 <i>Morsettiera 4+3</i> 	A Axial <i>Assiale</i> 	N Without cable gland <i>No pressacavo</i> 	-N Without cable <i>Senza cavo</i> 	- Standard PTO PTO always supplied <i>PTO sempre fornito</i>	-- Standard
		F Splicing connectors 1w+3w <i>Morsetto 1 cavo + 3 cavi</i> 	R Radial <i>Radiale</i> 	1 Stainless steel cable gland <i>Pressacavo in acciaio inox</i> 			
		U Universal <i>Universale</i> 	3 Anti-condensation cable gland <i>Pressacavo anticondensa</i> 	TA 2.5 m cable supplied with Δ connection <i>Cavo 2.5 m collegamento a Δ</i> 	1 PTC + (PTO) <i>Thermistor</i> 	-S Pre-heater <i>Scaldiglia</i> 	
- Without terminal box <i>Senza morsettiera</i> 	4 Anti-condensation valve <i>Valvola anticondensa</i> 	SB 5 m cable supplied with Y connection <i>Cavo 5 m collegamento a stella</i> 	2 PT100 + (PTO) <i>Thermal protection</i> 	-R Encapsulated resinated <i>Incapsulato resinato</i> 			
- Only for TEFC version <i>Solo per versione TEFC</i> - Without terminal box <i>Senza morsettiera</i> 	6 Stainless steel cable gland with Anti-condensation valve <i>Pressacavo in acciaio inox con valvola anticondensa</i> 	TB 5 m cable supplied with Δ connection <i>Cavo 5 m collegamento a Δ</i> 	Always supplied with cable <i>Sempre fornito con cavo</i>				